

# Induktherm rapid shrink VCS

Suitable for carbide and HSS tools

10kw



#### **Technical data**

Power: 10kw Size (mm):

Weight: 28kg

400V / 50Hz, 20A Supply:

## **Performance features**

- compact table-top device
- max. chuck length: 300mm
- Ø 3-32 (carbide shank)
- Ø 6-32 (HSS shank)



# Induction shrinking device for the fixing of carbide and HSS tools

With this redesign, well-proved components were partly taken over from previous models and summarized. In particular fixed places were created for the accessories, e.g. shrinking aids etc. so that in the working area of the device, order and handiness have a high significance.

With this device both carbide tools (of Ø3 - Ø32) as also steel in steel (of Ø6 - Ø32) can be shrunk. The corresponding parameters for time and performance are set aside in an internal database. This makes an overheating situation virtually impossible for a skilled operator.



### Quick-change adapter sockets

| HSK-A80       | Order no. | 990-356 |
|---------------|-----------|---------|
| HSK-A/E63     |           | 990-354 |
| HSK-A/E50     |           | 990-353 |
| HSK-A/E40     |           | 990-352 |
| HSK-A/E32     |           | 990-35  |
| HSK-E25       |           | 990-350 |
| SK40/BT40     |           | 990-354 |
| SK30/BT30     |           | 990-355 |
| PSC63         |           | 990-354 |
| others on red | quest     |         |
|               |           |         |



ST02/11

## Screening rings



Ø3 - Ø5 Art.-No. 990-605 Ø6 - Ø12 Art.-No. 990-612 Ø14 - Ø16 Art.-No. 990-616 Ø18 - Ø20 Art.-No. 990-620 Ø25 - Ø32 Art.-No. 990-632



ST02/11